

Safety Data Sheet
20S Grey Smooth Duct Sealant

SECTION I - IDENTIFICATION

PRODUCT NAME: 20S Grey Smooth Duct Sealant
PRODUCT CODE: 6624
PRODUCT USE: Duct Sealant
COMPANY NAME: QuestVapco Corporation
COMPANY ADDRESS: PO Box 624 Brenham, TX 77834
COMPANY PHONE: 1-800-231-0454
EMERGENCY PHONE: 800-255-3924

SECTION II – HAZARDS IDENTIFICATION

CLASSIFICATION: Does not present a hazard according to OSHA (29CFR 1910.1200)
HAZARD STATEMENT(S): None Known
This product contains the following percentage of chemicals of unknown toxicity: 60%
PRECAUTIONARY STATEMENTS: N/A
SYMBOL: N/A
HAZARDS NOT OTHERWISE CLASSIFIED: N/A

SECTION III – COMPOSITION/INFORMATION ON INGREDIENTS

HAZARDOUS INGREDIENT	CAS NUMBER	PERCENT
NJTS-50078-NCD	N/A	10-30%

SECTION IV - FIRST AID MEASURES

EYES: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
INGESTION: If swallowed: Rinse mouth. Do NOT induce vomiting. Get medical advice or attention.
INHALATION: If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell.
SKIN: If on skin: Wash with plenty of water. If skin irritation occurs: get medical attention.
ACUTE HEALTH HAZARDS: None Known
CHRONIC HEALTH HAZARDS: None known
NOTE TO PHYSICIAN: There is no specific treatment regimen. Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.

SECTION V – FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA: Not usually needed as product does not readily support combustion. Use media appropriate for fire's fuel source.
UNSUITABLE EXTINGUISHING MEDIA: N/A
SPECIAL FIRE FIGHTING PROCEDURES: Wear NIOSH approved Self Contained Breathing Apparatus with a full face piece operated in a positive pressure demand mode with full body protective clothing when fighting fires.
UNUSUAL FIRE AND EXPLOSION HAZARDS: N/A
HAZARDOUS COMBUSTION PRODUCTS: Oxides of carbon

SECTION VI – ACCIDENTAL RELEASE MEASURES

PERSONAL PROTECTIVE EQUIPMENT: Refer to section VIII for proper Personal Protective Equipment.
SPILL: Remove spill using an absorbent material.
WASTE DISPOSAL: Dispose of in accordance with federal, state, and local regulations. Materials should be recycled when possible. Waste may be regulated, may be landfilled at approved facility.
RCRA STATUS: Product should be fully characterized prior to disposal (40 CFR 261).

Safety Data Sheet
20S Grey Smooth Duct Sealant

SECTION VII – HANDLING AND STORAGE

HANDLING AND STORAGE: Store in a cool, dry area away from extremes of temperature. Keep container tightly sealed when not in use.

OTHER PRECAUTIONS: Keep out of the reach of children.

INCOMPATIBILITY: None Known

SECTION VIII – EXPOSURE CONTROLS/PERSONAL PROTECTION

HAZARDOUS INGREDIENT	OSHA PEL	ACGIH TLV
NJTS-50078-NCD	N/A	N/A

ENGINEERING CONTROLS / VENTILATION: General ventilation adequate.

RESPIRATORY PROTECTION: If used as a spray or airborne, respirator may be needed.

PERSONAL PROTECTIVE EQUIPMENT: Safety glasses

ADDITIONAL MEASURES: Wash hands thoroughly after handling.

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Off-White Caulk material

ODOR: Mild to No Odor

ODOR THRESHOLD: N/A

BOILING POINT: N/D

FREEZING POINT: N/D

FLAMMABILITY: Not considered a flammable liquid by OSHA (29CFR 1910.1200)

FLASH POINT: > 200°F (93°C)

AUTOIGNITION TEMPERATURE: N/D

LOWER FLAMMABILITY LIMIT: N/D

UPPER FLAMMABILITY LIMIT: N/D

VAPOR PRESSURE (mm Hg): Not Established

VAPOR DENSITY (AIR=1): N/A

EVAPORATION RATE: < 0.8 (Slow)

SPECIFIC GRAVITY (H2O=1): 1.31

pH: N/A

SOLIDS (%): 66%

SOLUBILITY IN WATER: Soluble

PARTITION COEFFICIENT: n-OCTANOL/WATER (K_{ow}): N/D

VOLATILITY INCLUDING WATER (%): 34%

VOLATILE ORGANIC COMPOUNDS (VOC): 0%

DIELECTRIC STRENGTH (Volts): N/A

DECOMPOSITION TEMPERATURE: N/D

VISCOSITY: 280,000 cps

SECTION X – STABILITY AND REACTIVITY DATA

REACTIVITY: N/A

CHEMICAL STABILITY: Stable

CONDITIONS TO AVOID: Do not mix with strong acids.

INCOMPATIBILITY: None Known

HAZARDOUS DECOMPOSITION OR BY-PRODUCT: Oxides of carbon

POSSIBLE HAZARDOUS REACTIONS: None Known

SECTION XI – TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: Not Established

ROUTES OF ENTRY: Eyes, Ingestion, Skin

EYES: Causes irritation, blurred vision.

Safety Data Sheet
20S Grey Smooth Duct Sealant

INGESTION: Causes gastrointestinal irritation.

INHALATION: Not likely due to low vapor pressure.

SKIN: Causes mild irritation with prolonged exposure.

MEDICAL CONDITION AGGRAVATED: None known

ACUTE HEALTH HAZARDS: None Known

CHRONIC HEALTH HAZARDS: None known

CARCINOGENICITY: OSHA: No ACGIH: No NTP: No IARC: No OTHER: CA Prop 65

SECTION XII – ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: Not Established

BIODEGRADABILITY: Component or components of this product are not biodegradable.

BIOACCUMULATION: This product is not expected to bioaccumulate.

SOIL MOBILITY: This product is mobile in soil.

OTHER ECOLOGICAL HAZARDS: None Known

SECTION XIII – DISPOSAL CONSIDERATIONS

WASTE DISPOSAL: Dispose of in accordance with federal, state, and local regulations. Materials should be recycled when possible.

Waste may be regulated, may be landfilled at approved facility.

RCRA STATUS: Product should be fully characterized prior to disposal (40 CFR 261).

SECTION XIV - TRANSPORTATION INFORMATION

PROPER SHIPPING NAME: Caulking liquid, n.o.s. Not Regulated

HAZARD CLASS/DIVISION: None

UN/NA NUMBER: N/A

PACKAGING GROUP: None

AIR SHIPMENT

PROPER SHIPPING NAME: Caulking liquid, n.o.s. Not Regulated

HAZARD CLASS/DIVISION: None

UN/NA NUMBER: N/A

SHIPPING BY WATER:

VESSEL (IMO/IMDG)

PROPER SHIPPING NAME: Caulking liquid, n.o.s. Not Regulated

HAZARD CLASS/DIVISION: None

UN/NA NUMBER: N/A

ENVIRONMENTAL HAZARDS WATER: N/A

SECTION XV - REGULATORY INFORMATION

TSCA STATUS: All Chemicals are listed or exempt.

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): None

SARA 311/312 HAZARD CATEGORIES: None

SARA 313 REPORTABLE INGREDIENTS: None

STATE REGULATIONS: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm: NJTS-500078-NCD.

INTERNATIONAL REGULATIONS: All components are listed or exempted.

NFPA HEALTH: 1

NFPA FLAMMABILITY: 0

NFPA REACTIVITY: 0

NFPA OTHER: None

HMIS HEALTH: 1

HMIS FLAMMABILITY: 0

HMIS REACTIVITY: 0

HMIS PROTECTION: A

Safety Data Sheet
20S Grey Smooth Duct Sealant

SECTION XVI - ADDITIONAL INFORMATION

PREPARATION BY: Jonathon Jarvis

DATE PREPARED: 02/07/2014

REVISION DATE: 02/07/2014

N/A = Not Applicable; N/D = Not Determined

DISCLAIMER: To the best of our knowledge, information contained herein is accurate. However there is no assumption of liability for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazard which exists. The information contained in this SDS was obtained from current and reliable sources; however, the data is provided without any warranty, expressed or implied, regarding its correctness or accuracy. Since the conditions or handling, storage and disposal of this product are beyond the control of the manufacturer, the manufacturer will not be responsible for loss, injury, or expense arising out of the products improper use. No warranty, expressed or inferred, regarding the product described in this SDS shall be created or inferred by any statement in this SDS. Various government agencies may have specific regulations regarding the transportation, handling, storage, use, or disposal of this product which may not be covered by this SDS. The user is responsible for full compliance.